

ANNEXURE-III

(To be submitted in Price Bid Envelope)

(All pages must be duly signed by the bidders along with seal)

PRICE BID(Rates are inclusive of GST)

Construction of boundary wall at 132/33KV Joyma GSS

Sl. No.	Item Description	Unit	Quantity	Rate to be Quoted (Rs)	Amount (Rs)
1	Earthwork in excavation for foundation trenches of walls, retaining walls, footings of column, steps, septic tank etc. including refilling (return filling) the quantity as necessary after completion of work, breaking clods in return filling, dressing, watering and ramming etc. and removal of surplus earth with all lead and lifts as directed and specified in the following classification of soils including bailing out water where necessary as directed and specified.(A) Up to a depth of 2.00m below the existing ground level.(a) In ordinary soil	M ³	64.66		
2	Plain cement concrete works with coarse aggregate of sizes 13mm to 32mm in foundation bed for footing steps, walls, brick works etc. as directed and specified including dewatering if necessary, and curing complete (shuttering where necessary shall be measured and paid separately). (a) In prop 1cement: 3 sand :6 coarse aggregate by volume	M ³	4.85		
3	"Supplying, fitting and fixing in position reinforcement bars conforming to relevant I.S. Code for R.C.C. work/ R.B. walling including straightening, cleaning, cutting and bending to proper shapes and length as per details, supplying and binding with 20G annealed black wire and placing in position with proper blocks, supports, chairs, spacers etc. complete. (No extra measurement for lap, hook, chair, anchor etc. will be entertained in the measurement as they are included in the rate) (Upto 1st floor level) " a) From Primary Producer: TATA/SAIL/Esser Steel/ Jindal steel/Shyam steel/RINL c) ISI approved Mild steel reinforcement bar(M.S.Bar)67	Qntl.	46.68		
4	Providing form work of ordinary timber planking so as to give a rough finish including cantering, shuttering, strutting and propping etc., height of propping and cantering below supporting floor to ceiling not exceeding 4.0M and removal of the same for in-situ reinforced concrete and plain concrete work in: Foundation, footings, bases of columns, pile cap, raft and mass concrete works etc. (b) Using 25mm thick plank	M ²	57.28		
5	Sides of tie beams, grade beams etc. at or below ground level. (b) Using 25mm thick plank	M ²	167.31		
6	Columns, Pillars, Posts & Strut (a) Square, Rectangular, polygonal in plan or any shape like Tee/L etc. having plane vertical face (ii) Using 25mm thick plank	M ²	153.05		

7	Providing and laying plain/reinforced cement concrete works cement, coarse sand & 20mm downgraded stone aggregate including dewatering if necessary, and curing complete but excluding cost of form work and reinforcement for reinforced cement concrete work (form work and reinforcement will be measured and paid separately) (I) Using Mixer Machine (A) In substructure up to plinth level Foundation, footing, columns with base tie and plinth beam, pile cap, base slab, retaining walls, walls of septic tank, inspection pit and the like and other works not less than 100mm thick up to plinth level. N) Without using admixture, plasticiser a) M15 grade concrete or Prop. 1:2:4	M ³	19.29		
	(B) In super structure from plinth level up to 1st floor level. N) Without using admixture, plasticiser a) M15 grade concrete or Prop. 1:2:4	M ³	10.44		
8	1st class brick nogged wall in cement mortar including racking out joints and curing complete as directed in super structure above plinth up to 1st floor level (protruding M.S rod/Tor steel of column to be embedded in cement mortar and will be measured and paid separately) (A) 112mm thick brick wall "(a) In cement mortar in proportion 1:4.	M ²	536.00		
9	Brick work in cement mortar with 1st class brick including racking out joints and curing complete as directed. (II) In superstructure above plinth level up to 1st floor level. (b) In proportion 1:4.(1 cement:4 sand)	M ³	7.20		
10	15 mm thick Cement plaster in single coat on single or half brick wall for interior plastering up to 1st floor level including arises, internal rounded angles, not exceeding 80mm girth and finished even and smooth including curing complete as directed. b) In cement mortar 1:4	M ²	1340.50		
11	a) Applying one coat of cement primer of approved brand and manufacture on new wall surface after thoroughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth.	M ²	3400.00		
	b) Finishing wall with water proofing cement paint of approved brand and manufacture and of required shade on new wall surface (two coats) to give an even shade after thoroughly brooming the surfaces to remove all dirt and remains of loose powdered materials.	M ²	3400.00		
	Total Amount				
	Say(Inclusive of GST)				
In words:					

